



US009913943B2

(12) **United States Patent**
Fourt et al.

(10) **Patent No.:** **US 9,913,943 B2**
(45) **Date of Patent:** **Mar. 13, 2018**

(54) **TRIGGER ASSEMBLY FOR AN AUTOMATIC INJECTION DEVICE**

(71) Applicant: **Eli Lilly and Company**, Indianapolis, IN (US)

(72) Inventors: **Jesse Arnold Fourt**, Menlo Park, CA (US); **Bradley James Simpson**, Oakland, CA (US)

(73) Assignee: **Eli Lilly and Company**, Indianapolis, IN (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 384 days.

(21) Appl. No.: **14/770,890**

(22) PCT Filed: **Mar. 7, 2014**

(86) PCT No.: **PCT/US2014/021496**

§ 371 (c)(1),

(2) Date: **Aug. 27, 2015**

(87) PCT Pub. No.: **WO2014/159018**

PCT Pub. Date: **Oct. 2, 2014**

(65) **Prior Publication Data**

US 2016/0008540 A1 Jan. 14, 2016

Related U.S. Application Data

(60) Provisional application No. 61/782,929, filed on Mar. 14, 2013.

(51) **Int. Cl.**
A61M 5/20 (2006.01)

A61M 5/315 (2006.01)

(52) **U.S. Cl.**
CPC **A61M 5/2033** (2013.01); **A61M 5/3158** (2013.01); **A61M 5/31501** (2013.01);
(Continued)

(58) **Field of Classification Search**

CPC **A61M 5/2033**; **A61M 5/31581**; **A61M 5/3158**; **A61M 5/31501**; **A61M 2205/19**; **A61M 2005/2073**

See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,752,918 A 7/1956 Uytenbogaart
4,561,856 A 12/1985 Cochran

(Continued)

FOREIGN PATENT DOCUMENTS

EP 0470977 2/1992
EP 0653220 5/1995

(Continued)

OTHER PUBLICATIONS

Patent Cooperation Treaty International Search Report and Written Opinion of the International Searching Authority pertaining to International Application No. PCT/US2014/021496. Dated May 20, 2014.

Primary Examiner — Kevin C Sirmons

Assistant Examiner — Amber Stiles

(74) *Attorney, Agent, or Firm* — M. Daniel Spillman

(57) **ABSTRACT**

A trigger assembly for an automatic injection device which by its operation releases a biased element of the device for movement. The trigger assembly includes a button pressable by a user, and a lock member. Prior to the button being plunged, a blocking element on the button is abutted by a button-engaging surface of the lock member to prevent lock member rotation, thereby allowing an engagement surface on the lock member to remain in engagement with an engagement surface of the biased element so as to restrain motion of the biased element. When the button is plunged, the blocking surface moves clear of the button-engaging surface to allow the lock member to rotate, during which

(Continued)

